

REGISTERED

BJCL/Bhilai/ Evt. /609

3rd June, 2020

The Member Secretary
Chhattisgarh Environment Conservation Board,
Paryavas Bhavan, North Block,
Sector-19, Nava Raipur Atal Nagar
Raipur (CG) - 492002

Sub : Environmental Statement for the Financial Year 2019- 20.

Dear Sir,

We are herewith submitting the Environmental Statement for the financial year ending
31st March, 2020 in **Form V** in Compliance of Environment (Protection) Rules 1986 as
amended subsequently.

Thanking you

Yours faithfully


Niraj Shrivastava (Unit Head)
Authorized Signatory

For Bhilai Jaypee Grinding Plant, Bhilai
(A Unit of Bhilai Jaypee Cement Limited)

CC: Regional Officer
Regional Office,
C.E. Conservation Board,
Bhilai, Durg (CG)



Plant : BSP Premises, Slag Yard Road (Opp. Sector-4, NMOH) Bhilai - 490 001,
Distt.-Durg(Chhattisgarh) Exchange-0788-4022255/56, Fax:0788-4022216
Regd. Office : Post Babupur, Satna (M.P.) Pin - 485112 Ph. :+91(7672) 415500L 415600
Head Office : 'JA House', 63 Basant Lok, Vasant Vihar, New Delhi - 110 057 (India)
Ph. : +91 (11) 26141540, 26147411 Fax : +91 (11) 26145389, 26143591

A JV of SAIL & JAIPRAKASH ASSOCIATES LIMITED



M/S. BHILAI JAYPEE GRINDING PLANT, BHILAI
(A UNIT OF BHILAI JAYPEE CEMENT LIMITED)
(JOINT VENTURE WITH SAIL)

ENVIRONMENTAL **STATEMENT**

For the Financial year ending
31st March 2020

M/S. BHILAI JAYPEE GRINDING PLANT, BHILAI
(A UNIT OF BHILAI JAYPEE CEMENT LIMITED)
(JOINT VENTURE WITH SAIL)

ENVIRONMENTAL STATEMENT

(For the Financial year ending 31st March 2020)

Contents

<u>S.No.</u>	<u>Description</u>	<u>Page No.</u>
1	General Information	Part A 01
2	Water & Raw material consumption	Part B 01 & 02
3	Pollution discharge to Environment / Unit of output	Part C 03 & 04
4	Hazardous waste	Part D 05
5	Solid Waste	Part E 06
6	Characterizations of Hazardous waste as well as solid waste & disposal practice	Part F 07
7	Impact of the pollution abatement measures taken on conservation of natural resources & on the cost of production	Part G 07 & 08
8	Additional measure / Investment proposal for environmental protection.	Part H 08
9	Any Other particulars for improving the quality of the environment.	Part I 09
10	Annexure- 1 – Ambient Air Quality	10

BHILAI JAYPEE GRINDING PLANT, BHILAI
F O R M - V
(See Rules 14)
Environmental Statement for the Financial
Year ending 31st March 2020

P A R T – A

- (i) Name and address of the owner/ : **BHILAI JAYPEE GRINDING PLANT**
Occupier of the industry : **BSP Premises, Slag Yard Road**
Operation or Process. : **(Opp. Sector – 4, Near NMOH)**
BHILAI, DURG -490001
- Occupier : **Shri R.B. Singh Ji**
- (ii) Industry Category : **Secondary (SIC Code)**
Primary (STC Code)
Secondary (SIC Code)
- (iii) Production Capacity : **2.2 Million Tonnes /Annum of**
Portland Slag Cement
- (iv) Year of establishment : **June 2010**
- (v) Date of the last Environmental : **6th June, 2019**
Statement Submitted

PART – B

WATER AND RAW MATERIALS CONSUMPTION

- (i) Water Consumption, m³ / day (Avg.)
- | | |
|----------|---|
| Process | : NIL |
| Cooling | : 12.9 (Based on 366 Days including dust suppression) |
| Domestic | : 48.4 (Based on 366 Day including plantation) |

Name of Product	Process Water Consumption per unit of product output	
------------------------	---	--

	During the previous financial year 2018-19	During the current financial year 2019-20
Portland Slag Cement	0.156 m ³ /T of Cement	0.124 m ³ /T of Cement

Water used for cooling purpose only. Water used for cooling purpose only.
(Excluding Domestic consumption)

II -Raw Materials Consumption

Name of the Raw Materials	Name of product	Consumption of raw material per unit of output	
		During the Previous financial year <u>2018-19</u>	During the Current financial year <u>2019-20</u>
Portland Slag Cement		MT/ MT of Cement Prodn.	MT / MT of Cement Prodn.
1. Clinker		0.39515	0.42298
2. Gypsum		0.01136	0.01823
3. Slag		0.57692	0.53578
4. Coal		0.01647	0.01794

PART- C**POLLUTION DISCHARGED TO ENVIRONMENT/UNIT OF OUTPUT****(Parameter as specified in the consent issued)****(a) Water**

Pollutants	Quantity of Pollutants Discharged (mass /day)	Concentration of Pollutants Discharges (mass/volume)	%of varia- tion from prescribed standards with reasons
-------------------	--	---	---

- NOT APPLICABLE -

This is a Cement Grinding Unit and Portland Slag Cement is produced by dry grinding of clinker and slag with small quantity of gypsum, hence no Industrial Waste Water is being generated from the plant process. Water is used only for cooling purpose which is recycled back into the system.

Domestic Waste Water generated from the office toilet is small quantity and the same is being disposed off into the Sewage line of Bhilai Steel Plant which finally is treated in their Sewage Treatment Plant.

<u>(b) AIR.</u>			
Pollutants	Allowable Standards	Concentration of Pollutants Discharged in mg/Nm³	Percentage of variation from prescribed Standards with reason
<u>Stack Emission.</u>		Min. Max. Avg.	
Stack of Bag house Cement Mill No.1&2 P.M.	30mg/Nm³	22.1– 25.7 (24.1)	Stack emission values are well within the prescribed limits stipulated by SPCB in Consent
Stack of packing plant Bag Filter No-1 P.M.	30mg/Nm³	18.0 – 20.7 (19.0)	Stack emission values are well within the prescribed limits stipulated by SPCB in Consent
Stack of packing plant Bag Filter No-2 P.M.	30mg/Nm³	18.4 – 22. (19.9)	Stack emission values are well within the prescribed limits stipulated by SPCB in Consent
Stack of packing plant Bag Filter No-3 P.M.	30mg/Nm³	18.2 – 18.6 (18.4)	Stack emission values are well within the prescribed limits stipulated by SPCB in Consent
Stack of packing plant Bag Filter No-4 P.M.	30mg/Nm³	19.2 – 19.2 (19.2)	Stack emission values are well within the prescribed limits stipulated by SPCB in Consent

Note- Ambient Air Quality Data as Annexure-1

P A R T – D**Hazardous Waste**

(As specified under Hazardous Waste (Management, Handling and Transboundary Movement) Rules, 2008)

Hazardous Waste	Total Quantity (kg)	
	During the previous Financial year 2018- 19	During the Current Financial year 2019-20
(a) From Process Spent Oil (Used Oil)	Nil.	Nil.
(b) From pollution Control Facilities	Nil.	Nil.

[06]

P A R T – E

SOLID WASTE

----- Total Quantity in MT -----		
	During the previous Financial year 2018 - 19	During the Current financial year 2019-20

(a) From Process	Nil (Burst Bags)	Nil (Burst Bags)
(b) From Pollution control Facilities	NIL	NIL
(c) (1) Quantity recycled or reutilized Within the unit	All the collected swept solid waste is reused in the the process	
(2) Sold	Nil (Burst Bags)	Nil (Burst Bags)
(3) Disposed	NIL	NIL

Dust collected in the Bag House and Bag filters are Recycled back into the system

P A R T – F

Please specify the characterization (in term of composition and quantum) of Hazardous as well as solid waste and indicate disposal practice adopted for both these categories of wastes.

HAZARDOUS WASTE.

This is a Cement Grinding Unit and Portland Slag Cement is produced by dry grinding of clinker and slag with small quantity of gypsum. No Hazardous waste is generated from the process except used oil which is collected from machineries. Presently used oil is stored in 200/220 liter capacity drums and kept in secured area / place within the factory premises as per the Hazardous Waste Management Rules. After getting the authorization of Hazardous Waste (Authorization No. 40/HO/HSMD/CECB/RAIPUR Dated 06/11/2012) and renewal of authorization - 204/HO/HSMD/CECB/RAIPUR date 12.12.2017 from the Board, the disposal is being done as per Hazardous & Other Wastes (Management and Transboundary Movement) Rules , 2016. The Used Oil disposed off to the Authorized recyclers approved by the CECB for processing.

E-WASTE. Nil (No any E- Waste disposed)

SOLID WASTE.

Burst bags are collected, stored in specific area and sold to recyclers.

Dust collected in the Bag House and Bag filters is recycled back into the system.

Part-G**Impact of pollution abatement measures taken on conservation of natural resources and on the cost of production.**

Bhilai Jaypee Cement Grinding plant is using slag generated by Bhilai Steel Plant to manufacture Portland Slag Cement, thus utilizing industrial waste and conserving limestone and coal-the non-renewable natural resources. The plant is equipped with state-of-the art Air Pollution Control devices so that emission level maintained well below stipulated norms as prescribed in the consent Total 34 Nos. of Bag filters including Bag House have been installed to control the Stack emission and at various material transfer points to control the fugitive dust emissions as per CPCB guideline. Entire collected dust is also recycled/ reutilized into the system. Fully mechanized system developed for handling of raw materials. All raw materials handling is being done by fully covered conveyor belt. Water sprinkling on road is being carried out regularly to control the fugitive dust emission which is generated during movement of vehicles.

Good housekeeping practice is being done by

1. Raw coal is stored in covered shed
2. Clinker and cement is being stored in covered silo.
3. Gypsum is stored in covered shed.
4. Regular road sweeping is being carried out.
5. Scheduled maintenance and monitoring of Pollution Control Devices is being done.

PART – H

Additional measures/ investment proposal for environmental protection including abatement of pollution, and Prevention of Pollution.

Company has been installed and commissioned Continuous Online Ambient Air Quality Monitoring Systems and Continuous Online Emission Monitoring System.

The ecology of the area has improved due to Green Belt development programme undertaken by the plant. So far, approx 11000 trees in total have been planted over an area of 4.62 ha and outside the plant area.

For the pollution control measures the company incurred a cost of Rs. 305.0 per ton of Cement production during 2019-20. This does not include capital investment for installation of Pollution Control devices.

ADDITIONAL MEASURES

1. Bag filters maintenance are done regular basis..
2. Permanent water sprinklers near wagon tippler area have been provided for dust suppression.
3. Used batteries are placed in designated place and send to only authorized recycler.
4. The parking area of cars and two wheeler inside plant has been concreted to control fugitive emission during movement.
5. Cleaning of rain water harvesting pits done.
6. Check dam made near coal storage area to restrict the spillage of coal in the drain

7. Skirt guard of some part of coal conveyer belt replaced to control fugitive emission.
8. Damaged nozzles of Water sprinklers in different places at feeding belts replaced.
9. Main Suction damper of Packer replaced to control dust.
10. Bag filter (491BF-1) discharge at Wagon tippler is redefined with air slide for proper cleaning and control dust emission.
11. Drum motor of Truck Loader-2 redefined & new inclined belt fitted to reduced the speed of bags dropping resulting minimize of dust emission.
12. Bag cleaning fan installed at packer radial discharge resulting minimized dust over bags during travels.

PART-I

Any other particulars for improving the quality of the Environment

1. The company has planted about 440 trees during the year 2019-20 in the plant premises and outside area. 4.62 Ha green belt area covered till date.
2. Revival & Proper care of trees/plants by top up of soil and fertilizer.
3. Periodic review of various Environmental Compliance conditions through Environmental Committee Meeting every month is being done.
4. 131 Numbers bag & 1 Numbers Cage Replaced and 35 solenoid valve repaired from Bag Filters & Bag Houses for controlling of dust emission effectively.
5. Water Sprinkling is being done on regular basis for dust suppression.
6. Awareness program and Tree plantation carried out on World Environment Day.
7. Awareness program carried out on International Ozone Day.
8. Awareness sessions carried out regarding Water conservation issues.

Ambient Air Quality
(2019-20)

<u>(b) AIR.</u>						
Pollutants	Allowable standards	Concentration of pollutants discharged in µg/m³			Percentage of variation from prescribed Standards with reason	
<u>1-Ambient Air</u>		Min.	Max.	Avg.		
<u>I. Switch Yard</u>						
i) S.P.M.	500µg/m ³	180.0	- 236.0	(214.0)	Well within the norms Well within the norms Well within the norms Well within the norms Well within the norms	
PM ₁₀	100µg/m ³	42.6	- 61.4	(55.2)		
PM _{2.5}	60µg/m ³	18.8	- 28.3	(23.8)		
ii) SO ₂	80µg/m ³	6.2	- 7.1	(6.8)		
iii) NOx	80µg/m ³	23.2	- 26.6	(24.8)		
iv) CO	4mg/m ³		- BDL-			
<u>II. Coal Yard</u>						
i) S.P.M.	500µg/m ³	185.0	- 254.0	(218.0)	Well within the norms Well within the norms Well within the norms Well within the norms Well within the norms	
PM ₁₀	100µg/m ³	44.3	- 66.9	(55.6)		
PM _{2.5}	60µg/m ³	18.5	- 29.7	(23.9)		
ii) SO ₂	80µg/m ³	6.2	- 7.8	(6.8)		
iii) NOx	80µg/m ³	22.2	- 26.7	(24.6)		
iv) CO	4mg/m ³		- BDL-			
<u>III. Wagon Tippler</u>						
i) S.P.M.	500µg/m ³	196.0	- 275.0	(241.0)	Well within the norms Well within the norms Well within the norms Well within the norms Well within the norms	
PM ₁₀	100µg/m ³	46.7	- 68.7	(60.2)		
PM _{2.5}	60µg/m ³	20.8	- 35.2	(29.3)		
ii) SO ₂	80µg/m ³	6.7	- 7.6	(7.1)		
iii) NOx	80µg/m ³	23.2	- 26.9	(25.2)		
iv) CO	4mg/m ³		- BDL-			
<u>IV. Auto workshop</u>						
i) S.P.M.	500µg/m ³	168.0	- 252.0	(209.0)	Well within the norms Well within the norms Well within the norms Well within the norms Well within the norms	
PM ₁₀	100µg/m ³	38.5	- 63.3	(43.1)		
PM _{2.5}	60µg/m ³	17.9	- 28.5	(22.5)		
ii) SO ₂	80µg/m ³	6.2	- 7.4	(6.8)		
iii) NOx	80µg/m ³	21.3	- 25.9	(24.2)		
iv) CO	4mg/m ³		- BDL-			